

HARDWARE FEATURES

Interface	3 10/100 RJ45 LAN Ports 1 10/100/1000 RJ45 LAN/WAN Port 1 RJ11 Port 1 USB 2.0 Port
Button	WPS Button Wireless On/Off Button Power On/Off Button Reset Button
Power Supply	12V/1.5A
IEEE Standards	IEEE 802.3 IEEE 802.3u 802.3ab
VDSL2 Standards	ITU G.993.2, Up to 17a profile (POTS) ITU-T G.993.5 (G.vector) ITU-T G.998.4 (G.INP)
ADSL Standards	Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1
ADSL2 Standards	ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis)
ADSL2+ Standards	ITU-T G.992.5
Dimensions (W x D x H)	243.5×167.5×32.7mm
Antenna Type	3 Fixed external antennas

WIRELESS FEATURES

Wireless Standards	IEEE 802.11a/n/ac 5GHz, IEEE 802.11b/g/n 2.4GHz
Wireless Speeds	867Mbps at 5GHz 300Mbps at 2.4GHz
Transmit Power	2.4GHz <20dBm(EIRP) 5GHz <23dBm(EIRP)
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA-PSK2 encryptions, Wireless MAC Filtering
Wireless Schedule	Support 2.4GHz and 5GHz Wireless Schedule

SOFTWARE FEATURES

Quality of Service	ATM QoS, Bandwidth Control
Security	NAT Firewall, Access Control, IP and MAC Address Binding
Operating Modes	VDSL/ADSL Modem Router, Wireless Router, 3G/4G Router
Management	Web Based Configuration(HTTP), Remote management, command Line Interface, SSL for TR-069, SNMP v1/2c, Web Based Firmware Upgrade, Diagnostic Tools
DHCP	Server, Client, DHCP Client List, Address Reservation, DHCP Relay
Port Forwarding	Virtual Server, Port Triggering, DMZ, ALG, UPnP
Dynamic DNS	DynDns, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec Passthrough
Protocols	Supports IPv4 and IPv6
ATM/PPP Protocols	ATM Forum UNI3.1/4.0, PPP over ATM (RFC 2364), PPP over Ethernet (RFC2516), IPoA (RFC1577/2225), MERIPoE (RFC 1483 Routed), Bridge (RFC1483 Bridge), PVC – Up to 8 PVCs
Advanced Functions	Parental Control, Network Address Translation(NAT), Port Mapping(Grouping), Static Routing, RIP v1/v2(optional), DNS Relay, DDNS, IGMP V1/V2/V3
USB Sharing	Support Samba(Storage)/FTP Server/Media Server/Printer Server, 3G/4G Modem
Guest Network	2.4GHz guest network, 5GHz guest network
IPSec VPN	Supports up to 10 IPSec VPN tunnels
Beamforming	5GHz

OTHERS

Certification	CE, RoHS, RCM
Package Contents	· AC1200 Wireless VDSL/ADSL Modem Router Archer VR400 · External Splitter · RJ11 DSL Cable · RJ45 Ethernet Cable · Power Adapter · Quick Installation Guide
System Requirements	· Microsoft Windows XP/7/8/8.1/10, MAC OS, NetWare, UNIX or Linux · Internet Explorer, Firefox, Chrome, Safari or other Java-enabled browser · Subscription with an Internet Service Provider (for Internet access)
Environment	· Operating Temperature: 0°C~40°C (32°F ~104°F) · Storage Temperature: -40°C~70°C (-40°F ~158°F) · Operating Humidity: 10%~90% non-condensing · Storage Humidity: 5%~90% non-condensing